

A2 SERIES

78 - 96 HP (58 - 70 KW)



RELIABLE POWER

High torque AGCO Power engine



HEAVY DUTY CONSTRUCTION

Well ballasted and rugged



PROVEN VALTRA PULLING POWER

Very strong drawbar and lift



MECHANICAL CONTROLS

Reliable and easy to use

VALTRA

YOUR WORKING MACHINE

A2 SERIES TECHNICAL SPECIFICATIONS

MODELS		A750	A850	A950
ENGINE				
Maximum power @ 2300rpm - Hp(kW)	ISO TR 14396	78 (58)	85 (63)	96 (70)
Maximum torque @ 1400rpm		296	316	340
Make		ACCO Power		
Number of cylinders		3		4
Displacement		3.300		4,400
Injection system		Bosch inline system		

CLUTCH	
Type	Independent Organic Double Disc
Disc Diameter	295
Operation	Mechanical

TRANSMISSION	
Transmission type	Mechanical
Position of levers	Side
Number of gears	8F + 4R / 12F + 8R / 16F + 8R / 12F + 12R

POWER TAKE OFF	
Type	Independent
Operation	Hydraulic
Speed options (rpm)	540 (std) or 540/540E or 540/1000
PTO Power (hp)	67 73 80

STEERING	
Type	Hydraulic

HYDRAULIC SYSTEM	
Maximum Pressure (kgf/cm ²)	180
Pump flow (l/min)	40
Maximum lifting capacity (kgf)	3860
Auxiliary Valves	2 double action valve
Separate transmission and auxiliary oil	25 litres

TYRES	
4x4	14.9 - 24 R1 / 18.4 - 34 R1

BRAKES	
Type	Multiple discs in oil bath
Engagement	Hydraulic

MODELS	A750	A850	A950
FUEL TANK			
Capacity	104		
WEIGHTS & DIMENSIONS			
Total length	3892		3892
Wheel base	2255		2450
Max Weight (kgf)	5280		
Min - max rear track width (mm)	1598 - 2124		

THEORETICAL SPEEDS (KM/H)							
Engine RPM				2.200			
Tyre				18.4 - 34 R1			
Gear	Standard (8F+4R)	Creep (12F+8R)		Multiplier (16F+8R)		Power Shuttle (12F+12R)	
		Tortoise	Hare	Tortoise	Hare	Gear	
L1	2,1	0,5	2,1	2,1	2,4	LL1	0,7
L2	2,9	0,7	2,9	2,9	2,3	LL2	1,0
L3	4,6	1,1	4,6	4,6	5,2	LL3	1,5
L4	6,0	1,5	6,0	6,0	6,9	LL4	2,1
H1	7,3	-	7,3	7,3	8,4	M1	2,8
H2	10,0	-	10,0	10,0	11,5	M2	4,1
H3	15,8	-	15,8	15,8	18,2	M3	6,0
H4	20,9	-	20,9	20,9	24,0	M4	8,5
						H1	9,6
R1	2,9	0,7	2,9	2,9	3,3	H2	14,2
R2	3,9	0,9	3,9	3,9	4,5	H3	20,8
R3	6,2	1,5	6,2	6,2	7,1	H4	29,5
R4	8,2	2,0	8,2	8,2	9,4		

OPTIONS *
3 double action valves
58 l/min hydraulic pump
Higher capacity hydraulic oil reservoir (40 l/min)
Front belly weights
Rear wheel weights included
Front and rear working lights
Bracket for number plate light
Fog lights
Warning triangle
Special seat
Pre-heating for the engine block
Front mudguards
* For more information, please contact your nearest Valtra dealer

This material contains a summary of product information, the specifications of which may change at any time without notice. The configuration of the standard version may differ from the illustrative photos. Therefore, before purchasing, always confirm all product information with your dealer.

 Valtra.africa/en

 [@ValtraAfrica](https://www.facebook.com/ValtraAfrica)

 [valtraglobal](https://www.instagram.com/valtraglobal)

 [Valtra](https://www.youtube.com/Valtra)

ACCO South Africa
16 Pomona Road, Kempton Park, Gauteng, 1619

VALTRA is a worldwide brand of **ACCO**.