A4 HITECH SERIES

128HP



RELIABLE ENGINE

High torque common-rail AGCO Power engine



COMFORT AND EASE

4 speed automatic transmission



CLASS LEADING HYDRAULICS

Load sensing closed centre system,



READY TO WORK

Guidance ready. Auto neutral braking





A4 HITECH SERIES TECHNICAL SPECIFICATIONS

MODELS		A134 HITECH
ENCINE		
	hp	128
Maximum power @ 2000rpm [ISO TR14396]	kW	96
Maximum Torque @1500 rpm	Nm	540
Maximum PTO Power	kW	84
Make	HVV	04
Number of cylinders		4
Displacement	Litres	44
Aspiration	Lities	Turbo Intercooler
Injection System		Common Rail
Engine Speed Memory		Standard
TRANSMISSION		otanuaru
Cears		16F + 16R
Clutch		Wet multi disc
Power shift		4 auto
Maximum speed	km/h	40
Forward reverse shuttle	niii/ii	Electro-hydraulic
4 Wheel Drive		Auto-engaging below 14km/h
Creeper		Auto engaging below itanii/ii
POWER TAKE OFF		
Engagement		Electro-Hydraulic
PTO Cruise Control		Standard
Speed	rpm	540 / 540E /1000
Engine Speed	rpm	1920 / 1550 / 1960
THREE POINT LIFT	1 pill	1020 / 1000 / 1000
Control		Electronic
Active transport suspension		Standard
Lift capacity	ΚN	50
STEERING		55
		Hydraulic
HYDRAULIC SYSTEM		,a
Туре		Closed Circuit - Load Sensing
Number of valves		3 + Power Beyond
Valve funtion		Double acting with float and flow divider
Maximum flow	I/min	105
	.,	1

MODELS		A134 HITECH
TYRES	•	
Front		14,9-28
Rear		18,4-38
BRAKES		
Туре		Multi disk oil immersed
Engagement		Hydraulic boosted
FUEL TANK		
Capacity	Litres	220
BALLAST		
Front	kg	15 x 55
Rear	kg	3 x 50 per wheel
WEIGHTS & DIMENSIONS		
Total length	mm	4822
Wheel Base	mm	2620
Maximum height	mm	2885
Clearance	mm	433
Maximum Permitted Weight	kg	7150
OPERATING ENVIRONMENT		
Operator station		Cab
Seat		Air
Auto guide		Ready

This material contains a summary of product information, the specifications of which may change at any time without notice. The configuration of the standard version may differ from the illustrative photos. Therefore, before purchasing, always confirm all product information with your dealer.













^{*} For more information, please contact your nearest Valtra dealer